



Boka Rea
Investments

Who We Are

Boka Rea Investments (PTY)(LTD) is an Engineering spares and equipment supplier partnered with reputable brands manufacturers to deliver customer's specific solution. We have both import and export experience. We offer engineering sales, services, spares and technical support to our customers. We currently service the mining industry, mineral processing plants, FMCG food processing plants and bulk water transfer companies

SOME OF OUR CLIENTS

- Valterra Platinum • Stibium Mine • Palabora copper
- Lebalelo Water User Association • Samancor Chrome • WilmarSA Gauteng and • Wilmar Processing KZN • Granor Passi • Sibanye-Stillwater

FOOD GRADE VALVES & PUMPS	GEAR DRIVE UNITS	CONTROL AND INSTRUMENTATION
AC DRIVES	AC ELECTRIC MOTORS	PIPES AND FITTINGS
GEARBOXES	PLC	MOTION CONTROLLERS
SERVO DRIVES	I/O MODULES	INDUSTRIAL VALVES AND PUMPS
		HMI



+27 78 097 4926

+27 15 004 1853

38 Kaye-Lyn St, Magna Via, Polokwane, 0700

www.bokarea.co.za

info@bokarea.co.za

INSAMCOR **VOSA** **atval** **Saunders** **WEG** **BIMAN**
SKG **VENT-O-MAT** **KINETROL** **burkert** **INOVANCE** **SEW**
the science inside **EURODRIVE**

+27 78 097 4926

www.bokarea.co.za

+27 15 004 1853

info@bokarea.co.za

38 Kaye-Lyn St, Magna Via, Polokwane, 0700

INSAMCOR  VOSA  Atval  Saunders  WEG  BIMAN 
SKG  VENT-O-MAT  KINETROL  burkert  INOVANCE  SEW 



A complete industrial automation portfolio

Our portfolio spans the complete range of industrial automation products including AC drives, servo drives & motors, PLCs & HMIs, motion control, CNCs, and industrial robots.



Atval - Heavy Duty Pinch Valves

Size range: DN40 – DN1500
Standard Pressure rating : PN10, PN16, PN25, PN40

Gearboxes

General purpose

- Crown and worm gearboxes from 10 to 1,600 Nm
- Helical gearboxes from 50 to 18,000 Nm
- Industrial gearboxes from 7,500 Nm to 500,000 Nm

Definite Purpose

- Plastic extruder
- Cooling tower
- Irrigation pivot
- Milk mixer



Industrial motors

General purpose

- Three-phase low voltage motors up to 1,250 kW

- Three-phase high voltage motors up to 1,800 kW

Definite purpose

- For energy efficiency:
- For hazardous areas:
- Ex db, Ex eb, Ex ec or Ex tb.
- For the mining industry
- For continuous processing industries
- For the food & beverage, pharmaceutical or other industry which requires continuous cleaning



Vent-O-Mat - RGXI Air release and Vacuum break Valves

Vent-O-Mat Series RBX "Anti-Shock", "ANTI-SURGE" RGX Sewage Air Release and vacuum Break Valve

SKG-HP up to 51 Bar – Bidirectional Slurry Knife Gate Valves

Size Range

- 3" – 24" (DN80 – DN600)

Pressure Rating

- 740 psi CWP (51 bar)

Body & Yoke

- Fusion bonded epoxy ductile iron (ASTM A536-84 Gr 60-42-10) body with fusion bonded epoxy coated angular support and cover plates



NCV - Nozzle Check Valve
Sizes 100mm-1200mm

Float Valves

Flow Control, Pressure Relief and Pressure Sustaining Valve

Sanitary Stainless Steel Butterfly Valve



Diaphragm Valves



Ball & Butterfly Sanitary Valves



Safety Valve



Centrifugal Pumps



Multistage Centrifugal Pumps



Hard Wall Slurry Hose



- Custom-manufacturing to suit your application's requirements
- Large bore hoses up to 1 200 mm internal diameter
- Pressure ratings up to 10 bar
- Operating temperature range from - 40° to 150° C

Gearmotors for agitators

The permissible overhung loads range from 25 000 N to 178 500 N and the motors corresponding with the relevant sizes vary in power from 0.12 kW to 200 kW. The maximum permitted gear unit output torque ranges from 820 Nm to 20 000 Nm.



Stainless Steel Flexible Hoses



Standard gear units and motors

Our standard gear units and motors are oriented towards the diversity of your application areas. Our modular system impresses with its robustness and reliability in every application scenario.

